

easy 
RESCUE PRO
AIS + DSC

easyRESCUE-PRO

If you can't find him
you can't save him



NEW:

Up to 8 MMSI programmable
for „closed loop“ distress call

AIS plus DSC
Get the best of both
technologies

AIS & DSC distress call:

Get the best of both to alert vessels about situation of distress.

If a „MAN OVER BOARD“ situation happens, you need to keep the victim in sight. It is essential for his survival.

The easyRESCUE-PRO has been developed from the well-known and approved AIS S.A.R.T. unit easyRESCUE. In addition to the AIS emergency functionality, the easyRESCUE-PRO has got a 2nd built-in communication alert: DSC distress call

By means of DSC distress call, other vessels with DSC controller aboard are able to provide support as a potential emergency responder.

It's a lightweight personal locating device which is fixed to clothing or lifejackets and which can be mounted onto a pole for use on a liferaft.

Function

Upon activation, the easyRESCUE -PRO unit starts transmitting AIS signals via VHF frequencies, providing the current GPS position along with COG, SOG and individual unit ID.

The victim's position is updated every minute and transmitted 8 times per minute for at least 96 hours.

As a result the crew of the ship will know exactly where the victim is, as well as every other ship with an AIS receiver within range. When the easyRESCUE-PRO's AIS message is received, it triggers an alarm on every AIS chart plotter with a worldwide standardized symbol. With accurate GPS data, a search-and-rescue can be initiated much faster.

Upon activation, in addition DSC distress call is sent automatically to the own ship of the victim. Once the „closed loop“ has been sent to the own vessel and there has been no acknowledgement for 10 minutes, an „open loop DSC distress call“ to every DSC receiver within range will be triggered. „Open loop“ transmission will be for-

warded to the coast guard by commercial vessels.

If there is an acknowledgement on DSC in the „closed loop“ or by a commercial vessel in „open loop“, DSC transmissions by easyRESCUE-PRO are terminated. In the meantime AIS messages are still being sent until the unit is completely switched off.

What is necessary to run the easyRESCUE-PRO?

The easyRESCUE-PRO needs no additional accessory. The device is ready to use, grab'n'go! An AIS receiver connected to a chart plotter is mandatory in order to receive and to display the AIS position report. A DSC radio unit is also mandatory to get the DSC distress call along with GPS coordinates of the victim.

Technical Data

AIS

- CE and R&TTE approval
- Transmission power: >2W
- Waterproof, IP68
- Operating conditions
-20°C - 55°C
- 96h (DSC acknowledged at once)
- Length 125mm, width 68mm, height 30mm.
- Weight approx. 350g
- Battery lifespan: 5 years (SOLAS standard)
- Service intervall:
 - * after usage
 - * after 5 years, in testing mode only

DSC

- Transmission power: >1W
- DSC frequency 156,525 Mhz

Made in Germany



- ≥24 hours of persistent transmission after activation with both technologies
- Closed & open loop acc. RTCM standard 11901.1

Highlights

- Automatic activation by water contact
- Automatic activation by rip cord mechanism with magnetic switch
- Simultaneous automatic activation of DSC distress call
- Up to 8 MMSI numbers for „closed loop“ to own ship or group of ships.
- After 10 minutes change to „open loop“, sending to all ships.
- Protection against unintended activation
- Mother ship knows where the victim is
- Mother ship receives DSC distress call
- GPS position is updated every minute
- 8 AIS messages per minute
- Ships with DSC controller can start search and rescue and /or relay the distress call
- Approval:
 - CE and R&TTE approval
 - BSH (for easyRESCUE)
 - SOLAS (for easyRESCUE)
- DSC according RTCM and Class D
- Range up to 15 nm (depending on height of receiving antenna)
- No royalties
- No time delays due to satellite communication
- Made in Germany by market leader



This product is available at:

for more information please visit
www.easyais.com



Excellence in Radio Technologies

Weatherdock AG

Sigmundstraße 180
D - 90431 Nürnberg
Tel.: +49 (0) 911 - 37 66 38 30
Fax: +49 (0) 911 - 37 66 38 40
Mail: info@weatherdock.de
URL: www.easyais.de

Stand: 08/2014 - Subject to alternation